

Frequency Range		Coupling	Coupling	I.L.	Directivity	VSWR	Power	Conn.	P/N
(GHz)		(dB)	Flatness	(dB)	(dB) min.	max.	In/Refl	Type	
			(dB)	max.			(watts)		
Min	Max		max.				max.		
0.5	1.0	20.0 ± 1.25	±0.75	0.20	25	1.15:1	50	SMA	CS20-01-436/3
0.5	1.0	20.0 ± 1.25	±0.75	0.20	22	1.15:1	50	N	CS20-01-436/3N
0.5	2.0	20.0 ± 1.00	±0.75	0.35	20	1.20:1	50	N	CS20-02-436/1N
0.5	2.0	20.0 ± 1.00	±1.00	0.35	23	1.20:1	50	SMA	CS20-02-436/2
1.0	2.0	20.0 ± 1.25	±0.75	0.20	25	1.10:1	50	SMA	CS20-03-436/7
1.0	2.0	20.0 ± 1.25	±0.75	0.20	20	1.10:1	50	N	CS20-03-436/7N
0.8	2,2	20.0 ± 1.25	±0.75	0.35	23	1.20:1	50	SMA	CS20-02A-436/3
0.8	2,2	20.0 ± 1.00	±0.75	0.35	20	1.20:1	50	N	CS20-02A-436/3N
0.8	2,5	20.0 ± 1.25	±0.70	0.40	20	1.20:1	50	SMA	CS20-22-436/3
1.0	4.0	20.0 ± 1.00	±0.75	0.40	23	1.20:1	50	SMA	CS20-04-436/13
1.0	4.0	20.0 ± 1.00	±0.75	0.40	18	1.20:1	50	N	CS20-04-436/13N
2.0	4.0	20.0 ± 1.25	±0.75	0.20	22	1.15:1	50	SMA	CS20-05-436/10
2.0	4.0	20.0 ± 1.25	±0.75	0.20	18	1.15:1	50	N	CS20-05-436/11N
3,6	4,2	20.0 ± 1.00	±0.30	0.50	15	1.40:1	50	SMA	CS20-06-435/3
3,6	4,2	20.0 ± 1.00	±0.30	0.50	18	1.40:1	50	N	CS20-06-436/11N
2,6	5,2	20.0 ± 1.25	±0.75	0.20	20	1.25:1	50	SMA	CS20-07-435/1
2,6	5,2	20.0 ± 1.25	±0.75	0.20	18	1.25:1	50	N	CS20-07-436/11N
5,8	6,4	20.0 ± 1.00	±0.30	0.50	15	1.40:1	50	SMA	CS20-08-435/1
5,8	6,4	20.0 ± 1.00	±0.30	0.50	18	1.40:1	50	N	CS20-08-436/11N
2.0	8.0	20.0 ± 1.00	±0.75	0.40	15	1.25:1	50	N	CS20-09-436/7N
2.0	8.0	20.0 ± 1.00	±0.75	0.40	20	1.25:1	50	SMA	CS20-09-436/9
4.0	8.0	20.0 ± 1.25	±0.75	0.25	20	1.30:1	50	SMA	CS20-10-435/1
4.0	8.0	20.0 ± 1.25	±0.75	0.25	17	1.30:1	50	N	CS20-10-436/11N
7,2	8,5	20.0 ± 1.00	±0.30	0.50	15	1.40:1	50	SMA	CS20-11-435/1
7,2	8,5	20.0 ± 1.00	±0.30	0.50	15	1.40:1	50	N	CS20-11-436/11N
0.5	12.0	20.0 ± 1.00	±0.80	1.00	15	1.50:1	25	SMA	CS20-19-436/19
4.0	12,4	20.0 ± 1.00	±0.40	0.50	17	1.30:1	50	SMA	CS20-14-436/15
7.0	12,4	20.0 ± 1.00	±0.50	0.30	17	1.30:1	50	SMA	CS20-12-435/1
7.0	12,4	20.0 ± 1.00	±0.50	0.50	15	1.30:1	50	N	CS20-12-436/11N
7,5	16.0	20.0 ± 1.25	±0.75	0.50	15	1.40:1	50	SMA	CS20-13-435/3
7,5	16.0	20.0 ± 1.25	±0.75	0.50	13	1.40:1	50	N	CS20-13-436/11N
0.5	18.0	20.0 ± 1.00	±1.00	0.90	0.5-12 GHz: 15 12-18 GHz: 12	1.50:1	25	SMA	CS20-23-436/20
1.0	18.0	20.0 ± 1.00	±0.50	0.80	1.0-12 GHz: 15 12-18 GHz: 12	1.50:1	25	SMA	CS20-18-436/16
1.0	18.0	20.0 ± 1.00	±0.50	0.80	1.0-12 GHz: 15 12-18 GHz: 12	1.50:1	25	N	CS20-18-436/16N
2.0	18.0	20.0 ± 1.00	±0.50	0.60	2.0-12 GHz: 15 12-18 GHz: 12	1.40:1	50	SMA	CS20-15-436/13
4.0	18.0	20.0 ± 1.00	±0.50	0.60	4.0-12 GHz: 15 12-18 GHz: 12	1.40:1	50	SMA	CS20-16-436/14
12,4	18.0	20.0 ± 1.00	±0.50	0.50	15	1.40:1	50	SMA	CS20-17-435/3
13,4	18.0	20.0 ± 1.00	±0.50	0.50	12	1.40:1	50	N	CS20-17-436/11N
8.0	20.0	20.0 ± 1.00	±0.80	1.00	12	1.50:1	25	SMA	CS20-21-435/3
6.0	25,5	20.0 ± 1.00	±0.80	0.70	13	1.55:1	20	2.92	CS20-50-435/4
0.5	27.0	20.0 ± 1.00	±1.20	1,80	14	1.50:1	20	2.92	CS20-56-436/20
0.5	40.0	20.0 ± 1.50	±1.50	2,20	12	1.60:1	20	2.92	CS20-57-436/20
1.0	40.0	20.0 ± 1.00	±1.50	1,60	10	1.80:1	20	2.92	CS20-53-436/13
2.0	40.0	20.0 ± 1.00	±1.00	1,60	10	1.80:1	20	2.92	CS20-52-436/9
6.0	40.0	20.0 ± 1.00	±1.00	1,20	10	1.70:1	20	2.92	CS20-51-435/4
6.0	50.0	20.0 ± 1.00	±1.00	1,60	10	2.00:1	20	2.40	CS20-54-435/4
6.0	60.0	20.0 ± 1.00	±2.00	1,80	7	2.50:1	20	1.85	CS20-55-435/4