

SCKTL50-2.4 High Precision Calibration Kit

(DC - 50GHz / 2.4mm)

Key Features

- Frequency Range: DC to 50 GHz
- VSWR : <1.15
- Calibration standards to perform full two-port calibration
- Adapters and torque wrench included
- >500 times Cycles



Overview

Saluki's SCKTL50-2.4 mechanical calibration kit contains precision standard devices to calibrate network analyzers in the 2.4mm interface. This kit also contains adapters to change the sex of the test port, and a torque wrench to ensure a repeatable reliable connection.

Model	Frequency	Spec.	List	qty.
SCKTL50-2.4 (Test Level)	DC - 50GHz	Open: $\pm 6^\circ$ Short: $\pm 4.5^\circ$ Load: VSWR<1.17 Adaptor: VSWR<1.15	Open: 2.4mm (M)	1
			Open: 2.4mm (F)	1
			Short: 2.4mm (M)	1
			Short: 2.4mm (F)	1
			Load: 2.4mm (M)	1
			Load: 2.4mm (F)	1
			2.4mm(f)-2.4mm(f)adaptor	1
			2.4mm(m)-2.4mm(m)adaptor	1
			2.4mm(m)-2.4mm(f)adaptor	1
Torque wrench	1			

SCKTL50-2.4 High Precision Calibration Kit

(DC - 50GHz / 2.4mm)

Material Information

Basic Data	
Interface	IEEE Std287
Mating Cycles	>500 cycles
Coupling Torque	0.9Nm
Open-End Wrench Size	8mm

Electrical Data	
Frequency	DC - 50GHz
Impedance	50 Ω
Average Power	$\leq 0.5W$

Materials	
Center Conductor	Au-plated Beryllim Copper
Body	Copper Plating / Staineless Stell, Passivated
Connector Nut	Stainless Steel, Passivated

Note: Information will conduct the necessary updates , the contents of this document are subject to change without notice