

SK500 Handheld Stabilized Laser Source

Wavelength: 850/1300/1310/1550nm



Key Features

- Support CW and a variety of modulation light output
- Adjustable output optical power , adjustment range 0 - 6dB, step 1dB (optional)
- Support automatic shutdown
- Support user self-calibration
- Backlight intelligent control
- Supports FC, SC, and ST interfaces
- Support single wavelength, combined wavelength customization

Saluki Handheld Stabilized Laser Source, mainly for fiber-optic network site installation, acceptance and maintenance of fiber optic cable, optical passive components of the transmission and loss measurement needs of the new design and development of products, with hand-held optical power meter use, can provide you with a fiber network precision test solution. According to user needs to provide 1 to 4 wavelengths of stable output, and with continuous power adjustable, modulated light output and other functions, backlight intelligent control, design more environmentally friendly energy. With a small shape, you can choose the backlight display and automatic shutdown function, with ultra wide optical power testing range.

SK500 Handheld Stabilized Laser Source

Wavelength: 850/1300/1310/1550nm

Technical Specifications

| Parameters | Specifications | |
|----------------------------------|--|---------------------|
| Wavelength range | 850/1300±20nm | 1310/1490/1550±20nm |
| Fiber Type | 62.5/125um | 9/125um |
| Optical connector | FC/SC/ST (FC-LC adapter option) | |
| Laser type | FP-LD | |
| Output power | ≥-5dBm | |
| Stability | ±0.02dB/8h | |
| Modulation mode | CW, 270Hz/1kHz/2kHz | |
| Power regulation | 0 - 6dB, 1dB step | |
| Operating temperature | -10℃ to +50℃ | |
| Storage temperature | -40℃ to +70℃ | |
| Relative humidity | 0 - 95% Non condensing | |
| Battery continuous working hours | ≥72h (LS function) | |
| Size | 186mm×100mm×50mm | |
| Power | Three AA batteries/ 1500mAh Lithium battery (optional) | |
| Net weight | 140g / 150g | |

Ordering Information

| Item | Module | Wavelength | Mark |
|-------------------------------------|--------|---|-------|
| SK500 Light Source (Dry Battery) | 1 | 1310/1550 nm | SM |
| | 2 | 850/1300 nm | MM |
| | 3 | 850/1300±20nm (MM) 1310/1550±20nm (SM) | SM&MM |
| | 4 | 1310/1490/1550 nm | SM |

No.367, Fuxing N. Rd.,105 Taipei,Taiwan Tel: +886.909 602 109

sales@salukitec.com www.salukitec.com



SK500 Handheld Stabilized Laser Source

Wavelength: 850/1300/1310/1550nm

| | | | |
|--|----|---|------------------------------------|
| SK500 Light Source (Rechargeable Li Battery) | 5 | 1310/1550 nm | SM |
| | 6 | 850/1300 nm | MM |
| | 7 | 850/1300±20nm (MM) 1310/1550±20nm (SM) | SM&MM |
| | 8 | 1310/1490/1550 nm | SM |
| SK500 Light Source (Adjustable) | 9 | 1310/1550 nm | SM (dry battery) |
| | 10 | 1310/1550 nm | SM (rechargeable Li battery) |
| | 11 | 850/1300±20nm (MM) 1310/1550±20nm (SM) | SM&MM (rechargeable Li battery) |
| | 12 | 850/1300±20nm | MM (dry battery) |

Standard Package

| Item | Name | Qty | Mark |
|------|-----------------|-----|--------------------------|
| 1 | SK500 host | 1 | |
| 2 | SC adapter | 1 | |
| 3 | User manual | 1 | |
| 4 | AA battery | 3 | Dry battery selected |
| 5 | Lithium battery | 1 | Lithium battery selected |
| 6 | Data line | 1 | Lithium battery selected |